



ESPECIFICACIONES	MODELO				
	EE-IED-2.6	EE-IED-2.8	EE-IED-3.9	EE-IED-6.25	EE-IED-10.42
Distancia de Píxel (Pitch)	P2.6~5.2mm	P2.8~5.6mm	P3.9~7.8mm	P6.25~12.5mm	P10.42~20.84mm
Densidad	73728 px/m ²	61952 px/m ²	32768 px/m ²	25600 px/m ²	9216 px/m ²
Brillo	3500 Nits	5000 Nits	5500 Nits	5000 Nits	4000 Nits
Método de conducción	Unidad estática de corriente constante				
Frecuencia de refresco	≥ 3840 Hz				
Escala de grises	Opción en 14bits o16bits				
Soporte (Hanging Bar)	Opcional				
Consumo máximo	800 W/m ²			750 W/m ²	600 W/m ²
Tamaño de la unidad (ancho x alto, mm)	Opción de 500x500mm, 500x1000mm o1500x500mm				
Peso	12Kg/m ²	12Kg/m ²	12Kg/m ²	10Kg/m ²	8Kg/m ²
Ángulo de visión	≥120°/ ≥120°				
Distancia de visualización	>3m	>3m	>4m	>7m	>10m
Temperatura de trabajo	-10°C to +45°C				
Tipo de mantenimiento	Trasero				
Vida útil	50000 horas				
Grado protección IP	IP32				
Transparencia	48%	55%	56%	60%	68%

